



Collections: Courtier Commercial Flooring | Commercail Waterproof Flooring

Commercial Moderate: EN 31 - Bedrooms, Hotels, Conference Rooms Small Offices

Commercial General: EN 32 - Classrooms, Small Offices, Hotels Boutiques

Width: 7”

Thickness: 5.5mm

Wear Layer: 20Mil (.5mm)

Length: 59”

Edge: Microbevel

Surface Texture: Various and EIR Wood Textures

Finish: Surface Guardian Pro UV Coating

Package: 28.51 sqft / carton; 60 cartons / pallet

Weight: 42.87 lbs./ carton

Warranty: 10 years Commercial Finish and 20 year Commercial Structural

FloorScore® Certificate: [Registration # SCS-FS-04192](#)

Trim Options: Multipurpose Reducer / T-Mold / Overlap Stair Nosing / Flush Stair Nosing

Installation Options: Float, and Over Radiant Heat* (*See full installation guide on hallmark-floors.com)

Cleaning Methods: Hallmark TrueClean Floor Cleaner

Flexibility (ASTM F137): Pass

Thickness Standard (ASTM F386) Pass

Resistance to Chemicals (5 minute standard) (ASTM F925 5): Pass

Resistance to Chemicals (24 hour standard) (ASTM F925): Pass

ASTM F925 - Stain Resistance: Pass

Heat Stability by Color Change (ASTM F1514): Pass

Light Stability by Color Change (ASTM F1515): Pass

Short Term Indentation (ASTM F1914) (PSI Equivalent > 5,500+ lbs.): Pass

Dimensional Stability after exposure to heat (ASTM F2199): Pass

Fire Resistance (ASTM E648): Class C - Pass

Coefficient of Friction (ASTM D-2047-04): Pass

Smoke Density (ASTM E662-09): Pass

Static Load (ASTM F970-07): Pass

Wear Resistance High (ASTM: F510-93) Pass

Emission (air) (ASTM F510-93): None Detected

Impact Sound Transmission (ASTM E492-09): 62 IIC