



# CHERRY SAVANNAH

Three strip design, silk matte finish, slight color variation.

## PRODUCT DETAILS

|                           |                           |
|---------------------------|---------------------------|
| <b>Article Number</b>     | 153N15CH50KW 0            |
| <b>Surface Treatment</b>  | Silk matte finish         |
| <b>Dimensions</b>         | 95 13/32 x 7 7/8 x 19/32" |
| <b>Weight per Package</b> | 51 lbs                    |
| <b>Area per Package</b>   | 31.32 sq ft               |
| <b>Area Per Board</b>     | 5.220 sq ft               |

## DETAIL DESCRIPTION

Even colour with minor variations. Small sized knots in limited numbers allowed.

## COLOUR CHANGE

Changes from pink hues to deeper reddish brown tones.

## FACTS

|                             |                              |
|-----------------------------|------------------------------|
| <b>Wood Species</b>         | Cherry                       |
| <b>Design</b>               | 3-strip                      |
| <b>Grading</b>              | Calm (City)                  |
| <b>Range</b>                | Kährs Original               |
| <b>Collection</b>           | American Naturals Collection |
| <b>Resandable</b>           | 2 times                      |
| <b>Natural/Stained</b>      | Natural                      |
| <b>Brinell Value</b>        | 3,6                          |
| <b>Joint</b>                | Woodloc® 5S                  |
| <b>Floor heating</b>        | Yes                          |
| <b>Warranty</b>             | 30 years                     |
| <b>Wear-layer material</b>  | Hardwood                     |
| <b>Wear-layer thickness</b> | 1/8"                         |
| <b>Core material</b>        | Pine/Spruce lamella          |
| <b>Thickness</b>            | 19/32"                       |
| <b>Installation method</b>  | Glue-Down, Floating          |

## TECHNICAL PROPERTIES

|                                   |             |             |
|-----------------------------------|-------------|-------------|
| <b>Moisture content</b>           | EN13183     | 7%±2%       |
| <b>Minimum Mean Density kg/m³</b> |             | >500 kg/m³  |
| <b>Reaction To Fire</b>           | EN13501-1   | Dfl-s1      |
| <b>Formaldehyde Emission</b>      | EN717-1     | E1          |
| <b>Content PCP</b>                | CEN/TR14823 | ≤ 5 x 10-6n |
| <b>Breaking Strength N/mm²</b>    | EN1533      | NPD         |
| <b>Thermal Conductivity</b>       | EN12664     | 0,14 W/mK   |
| <b>Thermal Resistance R-Value</b> |             | .11 (m2K/W) |
| <b>Biological Durability</b>      | EN350-2     | Class 1     |
| <b>CARB2</b>                      |             | Compliant   |

## CERTIFICATES

