



## CHEVRON DARK BROWN

Dark, strong brown floor with occasional knots, cracks and fillings. This product requires an, after installation, maintenance treatment using Kährs Satin Oil Matt.

Left version

### PRODUCT DESCRIPTION

<b>Article Number</b>	151XADEKWFKW18L
<b>Surface Treatment</b>	Oil
<b>Refining Treatment</b>	Beveled 4-sided, brushed, smoked

### DETAIL DESCRIPTION

Naturally occurring wood colour variations allowed, from light to dark brown. The product includes medium sound and black knots. Knots may vary in size and numbers.

### COLOUR CHANGE

Smoked product - noticeable color change over time.

### FACTS

<b>Wood Species</b>	White Oak
<b>Design</b>	Pattern
<b>Grading</b>	Lively (Country)
<b>Range</b>	Kährs ID
<b>Collection</b>	Chevron Collection
<b>Resandable</b>	2 times
<b>Natural/Stained</b>	Stained
<b>Brinell Value</b>	3, 7
<b>Joint</b>	Tongue & Groove
<b>Floor heating</b>	Yes
<b>Wear-layer material</b>	Hardwood
<b>Wear-layer thickness</b>	1/8"
<b>Core material</b>	Poplar
<b>Backside material</b>	Oak
<b>Thickness</b>	5/8"
<b>Installation method</b>	Glue-Down
<b>EAN Code</b>	7393969041898
<b>Surface Color</b>	Dark brown

### TECHNICAL PROPERTIES

<b>Moisture content</b>	EN13183	7%±2%
<b>Minimum Mean Density kg/m³</b>		>500 kg/m³
<b>Reaction To Fire</b>	EN13501-1	Dfl-s1
<b>Formaldehyde Emission</b>	EN717-1	E1
<b>Content PCP</b>	CEN/TR14823	≤ 5 x 10-6n
<b>Breaking Strength N/mm²</b>	EN1533	NPD
<b>Thermal Conductivity</b>	EN12664	0,14 W/mK
<b>Thermal Resistance R-Value</b>		.11 (m2K/W)
<b>Biological Durability</b>	EN350-2	Class 1
<b>CARB2</b>		Compliant

### CERTIFICATE

