



# OAK MUSE

Oak Moire have a 1-strip design, matt finish and some knots.

## PRODUCT DETAILS

<b>Article Number</b>	13103AEK1VKW185
<b>Surface Treatment</b>	Matte finish
<b>Refining Treatment</b>	Microbeveled 4-sided, Brushed
<b>Dimensions</b>	73 1/4 x 5 x 1/2"
<b>Weight per Package</b>	28 lbs
<b>Area per Package</b>	17,76 sq ft
<b>Area Per Board</b>	2.540 sq ft
<b>Package info</b>	Packages may contain start and stop boards.

## DETAIL DESCRIPTION

Even colour with minor variations. Small sized knots in limited numbers allowed.

## COLOUR CHANGE

Stained product - noticeable color change over time.

## FACTS

<b>Wood Species</b>	White Oak
<b>Design</b>	1-strip
<b>Grading</b>	Variation (Town)
<b>Range</b>	Kährs Avanti
<b>Collection</b>	Canvas Collection
<b>Resandable</b>	2 times
<b>Natural/Stained</b>	Stained
<b>Brinell Value</b>	3,7
<b>Joint</b>	Woodloc®
<b>Floor heating</b>	Yes
<b>Warranty</b>	25 years
<b>Wear-layer material</b>	Hardwood
<b>Wear-layer thickness</b>	1/8"
<b>Core material</b>	Pine/Spruce lamella
<b>Thickness</b>	1/2"
<b>Installation method</b>	Floating, Glue-Down

## TECHNICAL PROPERTIES

<b>Moisture content</b>	EN13183	7%±2%
<b>Minimum Mean Density kg/m<sup>3</sup></b>		>500 kg/m <sup>3</sup>
<b>Reaction To Fire</b>	EN13501-1	Dfl-s1
<b>Formaldehyde Emission</b>	EN717-1	E1
<b>Content PCP</b>	CEN/TR14823	≤ 5 x 10 <sup>-6</sup> n
<b>Breaking Strength N/mm<sup>2</sup></b>	EN1533	NPD
<b>Thermal Conductivity</b>	EN12664	0,08 W/mK
<b>Thermal Resistance R-Value</b>		.15 (m <sup>2</sup> K/W)
<b>Biological Durability</b>	EN350-2	Class 1
<b>CARB2</b>		Compliant

## CERTIFICATES

