




Kährs Combo System Underlayment

All in one underlayment with overlap seal in a 30 foot long roll covers 100 square feet for wood flooring install. Reduces sound, provides moisture protection under Kährs floating floors, and holds its shape under heavy loads. Kährs Combo System Underlayment provides a moisture barrier with mold reducing properties for use over concrete subfloor. Integral overlap flaps on Combo underlayment guards the wood flooring from moisture at the seams where the overlap flap has a peel and stick strip to aid the installation process. Sound rated Combo underlayment floor material is constructed of two-ply polyethylene film with flexible polystyrene granules sandwiched between to form a dual moisture barrier.

Combo System underlayer is approved for use under Kährs floating wood floors installed over radiant floor heating. Two size rolls of Kährs Combo underlayer are available. This roll covers floor area up to 100 square feet and the larger roll provides up to 630 square feet of floor coverage. Account for required cuts, overlap and wall run-up when figuring the number of underlayment rolls needed to complete the flooring job.

Kährs Combo System Floor Underlayment item 710100. 100 square foot roll

- 1/8 inch thick.
- 40 inches wide x 30 feet long roll.
- Covers 630 square feet of flooring.
- Combo underlayer R-Value = 0.39 R
- Sound Rating for Combo Underlayment System - STC = 67; IIC = 68
- Kährs Lifetime Guarantee eligible.



Kährs Combo System Underlayment item 710107. 630 square foot roll

- 1/8 inch thick.
- 40 inches wide x 189 feet long roll.
- Covers 630 square feet of flooring.
- Combo underlayer R-Value = 0.39 R
- Sound Rating for Combo Underlayment System - STC = 67; IIC = 68
- Kährs Lifetime Guarantee eligible.



NOTE: UNDERLAYMENT cannot be returned and is not refundable.

Kährs floating floor installation over radiant floor heat system must use either Kährs Combo Underlayment or QuietStride Underlayment. These products are warranty approved for Radiant Heat installations with the exception of Activity Floor.

Kährs installation instructions are the best guide for selecting the right underlayment to use on your Kährs flooring installation. Follow Kährs flooring guidelines for type of sub floor and subfloor moisture limits.

Specifications

Combo System Acoustical Abatement Specification - Kährs Specification The sound rated floor material shall be a two-ply polyethylene film with flexible polystyrene granules sandwiched between them providing a dual moisture barrier having a thickness of .118" (3 mm). It shall have a minimum compression set recovery of 80% (ASTM D 1055) without loss of resilience. The product shall have a minimum IIC rating of ____ (tested as per ASTM E-90 and E-492) based on the constructions detailed on the Kährs.com website. It shall be Combo System Underlayment from Kährs International, Inc. 940 Centre Circle, Suite 1000, Altamonte Springs, FL 32714.