



Kährs Eco + Underlayment

Kährs Eco+ underlayment with Vapor Bloc, 100 square foot coverage size, can be installed with floating or nail-down installation methods, film side up and fabric side down, to provide a breathable moisture barrier with antimicrobial protection. Excellent acoustic rating. Eligible for LEED green building points. UL GreenGuard GOLD Certified. Eco plus Vapor Bloc is free from formaldehyde, latex and PBDEs. Kährs Eco+ can be used under a nail down Kährs wood floor however be aware this application will compromise the vapor barrier. Eco plus with Vapor Bloc CANNOT be used for glue down floor installations. Eco + Underlayment lays with seams butted together.

Available in two size rolls, Eco+ can be found in kahrstore.com. This underlayment roll covers up to 100 square feet and the larger roll will fit a floor size up to 450 square feet.

- Eco+ 711100 - coverage: 100 sq ft - each roll is 36 inches wide x 33 feet long, 1/8 inch thickness.
 - Sound ratings: STC = 67; IIC = 73
 - LEED points eligible.
 - UL GreenGuard GOLD Certified.
 - 100% High density foam.
 - Approved for use over radiant heat subfloors.
-
- Eco+ 711450 - coverage: 450 sq ft per roll - roll size: 72 inches wide x 75 feet long, 1/8 inch thickness.
 - Sound ratings: STC = 67; IIC = 73
 - LEED points eligible.
 - UL GreenGuard GOLD Certified.
 - 100% High density foam.
- Approved for use over radiant heat subfloors.

NOTE: UNDERLAYMENT cannot be returned and is not refundable.

Kährs Eco+ Underlayment meets requirements for Kährs Lifetime Guarantee. Reference specific Kährs brand floor installation instructions for specified underlayment depending on type of installation and flooring material.

