



## OAK PALAZZO ROVERE

### PRODUCT DETAILS

<b>Article Number</b>	153138EK50KW 0
<b>Surface Treatment</b>	Silk matte finish
<b>Dimensions</b>	95 1/2 x 7 13/16 x 19/32"
<b>Weight per Package</b>	51 lbs
<b>Area per Package</b>	31.11 sq ft
<b>Area Per Board</b>	5.188 sq ft

### DETAIL DESCRIPTION

Even colour with minor variations. Sapwood may occur. Small sized knots in limited numbers allowed.

### COLOUR CHANGE

Some muting of colour variation to medium, straw brown.

### FACTS

<b>Wood Species</b>	White Oak
<b>Design</b>	Pattern
<b>Grading</b>	Variation (Town)
<b>Range</b>	Kährs Original
<b>Collection</b>	European Renaissance Collection
<b>Resandable</b>	2 times
<b>Natural/Stained</b>	Natural
<b>Brinell Value</b>	3,7
<b>Joint</b>	Woodloc® 5S
<b>Floor heating</b>	Yes
<b>Warranty</b>	30 years
<b>Wear-layer material</b>	Hardwood
<b>Wear-layer thickness</b>	1/8"
<b>Core material</b>	Pine/Spruce lamella
<b>Thickness</b>	19/32"
<b>Installation method</b>	Glue-Down, Floating

### TECHNICAL PROPERTIES

<b>Moisture content</b>	EN13183	7%±2%
<b>Minimum Mean Density kg/m³</b>		>500 kg/m³
<b>Reaction To Fire</b>	EN13501-1	Dfl-s1
<b>Formaldehyde Emission</b>	EN717-1	E1
<b>Content PCP</b>	CEN/TR14823	≤ 5 x 10-6n
<b>Breaking Strength N/mm²</b>	EN1533	NPD
<b>Thermal Conductivity</b>	EN12664	0,14 W/mK
<b>Thermal Resistance R-Value</b>		.11 (m2K/W)
<b>Biological Durability</b>	EN350-2	Class 1
<b>CARB2</b>		Compliant

### CERTIFICATES

