



## OAK ULF

Oak Ulf is a true rustic product where the surface is handcrafted and deeply brushed to enhance the beauty and specific characteristics of each and every board. Stained to a warm dark grey that gives it a rich color tone. Nature oil finished. This product must be oiled after installation and prior to use.

### PRODUCT DETAILS

<b>Article Number</b>	151N7BEKFBKW240
<b>Surface Treatment</b>	Oil
<b>Refining Treatment</b>	Beveled 4-sided, Handscraped, Brushed
<b>Dimensions</b>	95 9/32 x 7 3/8 x 19/32"
<b>Weight per Package</b>	49 lbs
<b>Area per Package</b>	29.27 sq ft
<b>Area Per Board</b>	4.878 sq ft

### DETAIL DESCRIPTION

All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

### COLOUR CHANGE

Stained product - noticeable color change over time.

### FACTS

<b>Wood Species</b>	White Oak
<b>Design</b>	1-strip
<b>Grading</b>	Dynamic
<b>Range</b>	Kährs Original
<b>Collection</b>	Founders Collection
<b>Resandable</b>	2 times
<b>Natural/Stained</b>	Stained
<b>Brinell Value</b>	3,7
<b>Joint</b>	Woodloc® 5S
<b>Floor heating</b>	Yes
<b>Warranty</b>	30 years
<b>Wear-layer material</b>	Hardwood
<b>Wear-layer thickness</b>	1/8"
<b>Core material</b>	Pine/Spruce lamella
<b>Thickness</b>	19/32"
<b>Installation method</b>	Glue-Down, Floating

### TECHNICAL PROPERTIES

<b>Moisture content</b>	EN13183	7%±2%
<b>Minimum Mean Density kg/m³</b>		>500 kg/m³
<b>Reaction To Fire</b>	EN13501-1	Dfl-s1
<b>Formaldehyde Emission</b>	EN717-1	E1
<b>Content PCP</b>	CEN/TR14823	≤ 5 x 10 <sup>-6</sup> n
<b>Breaking Strength N/mm²</b>	EN1533	NPD
<b>Thermal Conductivity</b>	EN12664	0,14 W/mK
<b>Thermal Resistance R-Value</b>		.11 (m2K/W)
<b>Biological Durability</b>	EN350-2	Class 1
<b>CARB2</b>		Compliant

### CERTIFICATES

