



## OAK LIMESTONE

### PRODUCT DETAILS

<b>Article Number</b>	153N0BEK0WKW 0
<b>Surface Treatment</b>	Matte finish
<b>Refining Treatment</b>	Brushed
<b>Dimensions</b>	95 13/32 x 7 7/8 x 19/32"
<b>Weight per Package</b>	51 lbs
<b>Area per Package</b>	31.32 sq ft
<b>Area Per Board</b>	5.220 sq ft

### DETAIL DESCRIPTION

Naturally occurring wood colour variations allowed, from light to dark brown. Will include sapwood. The product includes medium sound and black knots. Knots may vary in size and numbers.

### COLOUR CHANGE

Stained product - noticeable color change over time.

### FACTS

<b>Wood Species</b>	White Oak
<b>Design</b>	3-strip
<b>Grading</b>	Lively (Country)
<b>Range</b>	Kährs Original
<b>Collection</b>	Harmony Collection
<b>Resandable</b>	2 times
<b>Natural/Stained</b>	Stained
<b>Brinell Value</b>	3,7
<b>Joint</b>	Woodloc® 5S
<b>Floor heating</b>	Yes
<b>Warranty</b>	30 years
<b>Wear-layer material</b>	Hardwood
<b>Wear-layer thickness</b>	1/8"
<b>Core material</b>	Pine/Spruce lamella
<b>Thickness</b>	19/32"
<b>Installation method</b>	Floating, Glue-Down
<b>Surface Color</b>	White

### TECHNICAL PROPERTIES

<b>Moisture content</b>	EN13183	7%±2%
<b>Minimum Mean Density kg/m³</b>		>500 kg/m³
<b>Reaction To Fire</b>	EN13501-1	Dfl-s1
<b>Formaldehyde Emission</b>	EN717-1	E1
<b>Content PCP</b>	CEN/TR14823	≤ 5 x 10-6n
<b>Breaking Strength N/mm²</b>	EN1533	NPD
<b>Thermal Conductivity</b>	EN12664	0,14 W/mK
<b>Thermal Resistance R-Value</b>		.11 (m2K/W)
<b>Biological Durability</b>	EN350-2	Class 1
<b>CARB2</b>		Compliant

### CERTIFICATES

