



## OAK SMOKE

Light smoked, matt lacquered surface. Color variation due to smoking.

### PRODUCT DETAILS

<b>Article Number</b>	153N3REK09KW 0
<b>Surface Treatment</b>	Matte finish
<b>Refining Treatment</b>	Light smoked
<b>Dimensions</b>	95 13/32 x 7 7/8 x 19/32"
<b>Weight per Package</b>	51 lbs
<b>Area per Package</b>	31.32 sq ft
<b>Area Per Board</b>	5.220 sq ft

### DETAIL DESCRIPTION

Even colour with minor variations. Sapwood may occur. The smoked design is likely to enhance the naturally occurring wood color variations and create further contrast between light and dark. Small sized knots in limited numbers allowed.

### COLOUR CHANGE

Smoked product - noticeable color change over time.

### FACTS

<b>Wood Species</b>	White Oak
<b>Design</b>	3-strip
<b>Grading</b>	Variation (Town)
<b>Range</b>	Kährs Original
<b>Collection</b>	Harmony Collection
<b>Resandable</b>	2 times
<b>Natural/Stained</b>	Natural
<b>Brinell Value</b>	3,7
<b>Joint</b>	Woodloc® 5S
<b>Floor heating</b>	Yes
<b>Warranty</b>	30 years
<b>Wear-layer material</b>	Hardwood
<b>Wear-layer thickness</b>	1/8"
<b>Core material</b>	Pine/Spruce lamella
<b>Thickness</b>	19/32"
<b>Installation method</b>	Floating, Glue-Down

### TECHNICAL PROPERTIES

<b>Moisture content</b>	EN13183	7%±2%
<b>Minimum Mean Density kg/m³</b>		>500 kg/m³
<b>Reaction To Fire</b>	EN13501-1	Dfl-s1
<b>Formaldehyde Emission</b>	EN717-1	E1
<b>Content PCP</b>	CEN/TR14823	≤ 5 x 10-6n
<b>Breaking Strength N/mm²</b>	EN1533	NPD
<b>Thermal Conductivity</b>	EN12664	0,14 W/mK
<b>Thermal Resistance R-Value</b>		.11 (m2K/W)
<b>Biological Durability</b>	EN350-2	Class 1
<b>CARB2</b>		Compliant

### CERTIFICATES

