



ASH FLOW

The white structure and semi-transparent stain on this single-strip ash floor from the Lux Collection balances the light and dark contrasts in the wood, allowing the warm ash tones to softly filter through. Four-sided micro-bevelling at the edging ensures a classic full plank look and feel. Each board is carefully brushed to perfection to enhance the natural character of the grain. The light-absorbing, ultra-matt lacquer finish creates the impression of newly sawn timber, effectively eliminating glare while protecting the wood from daily wear.

PRODUCT DETAILS		FACTS		TECHNICAL PROPERTIES		
Article Number	151N8AAKG4KW240	Wood Species	Ash	Moisture	EN13183	7%±2%
Surface treatment	Ultra matt lacquer	Board	1-strip	content		
Design features	Microbevelled 4- sided, Brushed	Grading	Lively (Country)	Minimun Mean Density kg/m³		>500 kg/m ³
		Range	Kährs Original	Reaction To Fire	EN13501-1	Dfl-s1
Dimensions	2420 x 187 x 15 mm	Collection	Lux Collection	Formaldehyde	EN717-1	E1
Weight per Package	22 kg	Resandable	2-3 times	Emission	2117 17	
Area per Package	2.72 m ²	Natural/Stained	Stained	Content PCP	CEN/TR14823	≤ 5 x 10-6n
Area Per Board	0.453 m ²	Brinell Value	4,0	Breaking	EN1533	NPD
Package info	Packages may contain start and stop boards.	Joint	Woodloc® 5S	Strength N/mm²		
	•	Floor heating	Yes	Thermal Conductivity	EN12664	0,14 W/mK
DETAIL DESCRIPTION		Warranty	30 years	Thermal Resistance R-Value		11 (m2K/M)
Naturally occuring wood colour variations allowed, from light to dark brown. The product includes large sound and black knots. Knots may vary in size and numbers.		Wear-layer material	Hardwood			.11 (m2K/W)
		Wear-layer thickness	3.5 mm	Biological EN350-2 Durability		Class 1
		Core material	Pine/Spruce/Alder	CARB2		Compliant
COLOUR CHANGE		Thickness	15 mm			
		Installation method	Floating, Glue-down			
Stained product - noticeable color change over time		Surface Colour	White			

CERTIFICATES



