



KINDA

Earth greys on a warm base, balanced contrast and transparency. Hard brushed, very rustic board with highlighted knots and cracks.

PRODUCT DETAILS

Article Number	151NDSEK02KW240
Surface Treatment	Oil
Refining Treatment	Beveled 4-sided, Handscraped, Brushed, Saw marks
Dimensions	95 9/32 x 7 3/8 x 19/32"
Weight per Package	49 lbs
Area per Package	29.27 sq ft
Area Per Board	4.878 sq ft

DETAIL DESCRIPTION

All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

COLOUR CHANGE

The colour matures over time.

FACTS

Wood Species	White Oak
Design	1-strip
Grading	Expressive
Range	Kährs Supreme
Collection	Småland Collection
Resandable	2 times
Natural/Stained	Stained
Brinell Value	3,7
Joint	Woodloc® 5S
Floor heating	Yes
Warranty	30 years
Wear-layer material	Hardwood
Wear-layer thickness	1/8"
Core material	Pine/Spruce lamella
Thickness	19/32"
Installation method	Floating, Glue-Down
Surface Color	Earth Grey

TECHNICAL PROPERTIES

Moisture content	EN13183	7%±2%
Minimum Mean Density kg/m³		>500 kg/m³
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 x 10-6n
Breaking Strength N/mm²	EN1533	NPD
Thermal Conductivity	EN12664	0,14 W/mK
Thermal Resistance R-Value		.11 (m2K/W)
Biological Durability	EN350-2	Class 1
CARB2		Compliant

CERTIFICATES



FSC Certified