



## OAK BISBEE

Oak Bisbee is a 3-strip floor with moderate color variations and a brown stain. May contain minor knots.

### PRODUCT DETAILS

<b>Article Number</b>	133NABEK5MUW 0
<b>Surface Treatment</b>	Silk matte finish
<b>Dimensions</b>	95 13/32 x 7 7/8 x 1/2"
<b>Weight per Package</b>	54 lbs
<b>Area per Package</b>	36.60 sq ft
<b>Area Per Board</b>	5.220 sq ft

### DETAIL DESCRIPTION

Naturally occurring wood colour variations allowed, from light to dark brown. The product includes medium sound and black knots. Knots may vary in size and numbers.

### COLOUR CHANGE

Stained product - noticeable color change over time.

### FACTS

<b>Wood Species</b>	White Oak
<b>Design</b>	3-strip
<b>Range</b>	Kährs Avanti
<b>Collection</b>	Tres Collection
<b>Resandable</b>	2 times
<b>Natural/Stained</b>	Stained
<b>Brinell Value</b>	3,7
<b>Joint</b>	Woodloc® 5S
<b>Floor heating</b>	Yes
<b>Warranty</b>	20 years
<b>Wear-layer material</b>	Hardwood
<b>Wear-layer thickness</b>	7/64"
<b>Core material</b>	Pine/Spruce lamella
<b>Thickness</b>	1/2"
<b>Installation method</b>	Floating, Glue-Down

### TECHNICAL PROPERTIES

<b>Moisture content</b>	EN13183	7%±2%
<b>Minimum Mean Density kg/m³</b>		>500 kg/m³
<b>Reaction To Fire</b>	EN13501-1	Dfl-s1
<b>Formaldehyde Emission</b>	EN717-1	E1
<b>Content PCP</b>	CEN/TR14823	≤ 5 x 10 <sup>-6</sup> n
<b>Breaking Strength N/mm²</b>	EN1533	NPD
<b>Thermal Conductivity</b>	EN12664	0,14 W/mK
<b>Thermal Resistance R-Value</b>		.09 (m²K/W)
<b>Biological Durability</b>	EN350-2	Class 1
<b>CARB2</b>		Compliant

### CERTIFICATES

