



JARRAH SYDNEY

Three strip design, silk matte finish, color variation.

PRODUCT DETAILS

| | |
|---------------------------|---------------------------|
| Article Number | 153N15JH50KW 0 |
| Surface Treatment | Silk matte finish |
| Dimensions | 95 13/32 x 7 7/8 x 19/32" |
| Weight per Package | 51 lbs |
| Area per Package | 31.32 sq ft |
| Area Per Board | 5.220 sq ft |

DETAIL DESCRIPTION

Naturally occurring wood colour variations allowed, from light to dark red. Small sized knots in limited numbers allowed.

COLOUR CHANGE

Darkening towards deeper red/red browns.

FACTS

| | |
|-----------------------------|---------------------|
| Wood Species | Jarrah |
| Design | 3-strip |
| Grading | Calm (City) |
| Range | Kährs Original |
| Collection | World Collection |
| Resandable | 2 times |
| Natural/Stained | Natural |
| Brinell Value | 4,7 |
| Joint | Woodloc® 5S |
| Floor heating | Yes |
| Warranty | 30 years |
| Wear-layer material | Hardwood |
| Wear-layer thickness | 1/8" |
| Core material | Pine/Spruce lamella |
| Thickness | 19/32" |
| Installation method | Floating, Glue-Down |

TECHNICAL PROPERTIES

| | | |
|-----------------------------------|-------------|-------------|
| Moisture content | EN13183 | 7%±2% |
| Minimum Mean Density kg/m³ | | >500 kg/m³ |
| Reaction To Fire | EN13501-1 | Dfl-s1 |
| Formaldehyde Emission | EN717-1 | E1 |
| Content PCP | CEN/TR14823 | ≤ 5 x 10-6n |
| Breaking Strength N/mm² | EN1533 | NPD |
| Thermal Conductivity | EN12664 | 0,14 W/mK |
| Thermal Resistance R-Value | | .11 (m2K/W) |
| Biological Durability | EN350-2 | Class 1 |
| CARB2 | | Compliant |

CERTIFICATES

