

Kährs®

QUALITY IN WOOD SINCE 1857

TECHNICAL SPECIFICATION

KÄHRS WOOD FLOOR, 9/16" (14 MM) WOODLOC®

Kährs International
940 Centre Circle | Suite 1000
Altamonte Springs | Florida | 32714
Phone: 1 800 800 5247 | Fax: 407 260 9933
Email: info@kahrs.com

Areas of application and special characteristics

The 9/16"-thick board can be used in many different types of premises, but is most suitable for domestic applications.

- Dimensionally stable due to climate-controlled production.
- Woodloc® joint.
- Quick and easy installation as a result of precision manufacturing.
- High-quality wood floors that last for many years.
- Available in several different "colors" and wood species.
- Natural and unique design including beveled and square edge boards.
- Pre-finished in UV-cured enhanced urethane finish, making the floors more durable and easy to clean.

Construction

- 1-strip board with Woodloc® joint on all edges of the board.
- Surface layer consists of sawn strips.
- Bottom layer of spruce veneer.

Thickness of the surface layer

- approx. 1/8".

Surface treatment

- Pre-finished with UV-cured enhanced finish.
- Square or beveled edge.

Additional information

- Compliance to Formaldehyde emission class E1 and CARB Phase 1.
- Reaction to Fire (fire rating) classification Dfl -s1.
- CE-Group 450.

Requirements for the subfloor

The subfloor must be firm, flat, and free from moisture and debris. Please see detailed subfloor requirements and preparation procedures in the Kährs Professional Installation Guides that are available for download from our web site at www.kahrs.com (Download Library).

Maintenance

Detailed information about maintenance is described in our Floor Care Guide and Guarantee. Download it from our web site at www.kahrs.com (Download Library).

Moisture content

Moisture content when delivered: 7%.

Weight per carton

- 32 to 35lbs Eco Core
- 27lbs Plywood Core

Packaging

- 5 sided cardboard tray.
- Protective PE sheeting.

Pack contents

69.25 inches long / 5 inches wide
14.43 sft/carton
6 boards per carton