

Sicily Collection

PRODUCT DETAILS

| | |
|------------------------|--|
| Product Type | Rigid Engineered Luxury Vinyl |
| Collection | Sicily Collection |
| Construction | Solid Vinyl Tile |
| Classification | ASTM F3261-Grade 1, Type A-Smooth, Type B-Embossed |
| Overall Thickness | 5.5mm (0.2165") |
| Wear Layer | 22mil (0.55mm) |
| Underlayment | 1.5mm IXPE (0.0591") |
| Edge Profile | Painted Bevel |
| Surface Finish | Ceramic Bead |
| Embossing | Photo Match Embossing |
| Edge Profile | Easy-to-install with I4F Locking system |
| Size | 18" W x 36" L (457x935mm) |
| Square Feet Per Carton | 27.60 SQFT/CTN |
| Pieces Per Carton | 6 PIECES/CTN |
| Weight Per Carton | 21.79 KGS/CTN 48.04 LBS/CTN |
| Carton Per Pallet | 38 CTNS/PLT |
| Installation Method | Floating/Glue Down |

TECHNICAL PROPERTY


| | |
|---------------------------------|--|
| Dimensional Stability | ASTM F2199 - Passes - $\leq 0.2\%$ / lineal ft. (305 mm) |
| Curling | ISO 23999 - Passes - $\leq 2\text{mm}$ |
| Static Load | ASTM F970 - Passes - $\leq 0.005"$ (0.13mm) (without underlayer) |
| Static Load Limit | SIM Test - 1000 psi (0.02mm) (without underlayer) |
| Residual Indentation | ASTM F1914 - Passes - Average: $\leq 0.007"$ (0.18mm) (without underlayer) |
| Resistance to Chemicals | ASTM F925-Passes-No more than a slight change in surface |
| Resistance to Heat | ASTM F1514 - Passes - Average $\Delta E < 8.0$ |
| Resistance to Light | ASTM F1515 - Passes - Average $\Delta E < 8.0$ |
| Critical Radiant Flux | ASTM E648 - Passes - Class I: $\geq 0.45 \text{ W/Sq.cm}$ |
| Smoke Density | ASTM E662 - Passes - Flaming & Non Flaming ≤ 450 |
| VOCs/TVOCs, Formaldehyde | CDPH/EHLB Method v1.2 Compliant |
| Substances of Very High Concern | REACH SVHC 191 - Passes - Per Substance: $\leq 0.1\% \text{ w/w}$ |
| Heavy Metals | ASTM F963 - Passes |
| Phthalates | ASTM D7823 - Passes - CPSC-CH-C1001-09.3 |
| Slip Resistance | ASTM D2047- Dry: 0.38 Wet: 0.90 |
| Fungi Resistance | ASTM G21-15 - Passes |
| IIC Rating | ASTM E492 & ASTM E989 - Result: 70 |
| STC Rating | ASTM E90 & ASTM E413 - Result: 67 |

SUSTAINABILITY

| | |
|-----------------------------------|--------------------------------|
| Material | Virgin Vinyl |
| Certification | Floor Score® certified |
| Environmental Product Declaration | EPD Vinyl Click |
| Health Product Declaration | HPD 2.1 Vinyl Click - 1000 ppm |

SERVICE


| | |
|------------|---------------------------|
| Warranties | Limited Lifetime Warranty |
|------------|---------------------------|



2101 Carrara



2102 Pietra



2103 Salso



2104 Tarto



2116 Gela



2117 Simeto

