

Temple Collection

PRODUCT DETAILS

Product Type	Rigid Engineered Luxury Vinyl
Collection	Temple Collection
Construction	Residential Grade Rigid Vinyl Plank
Classification	ASTM F3261-Grade 1, Type A-Smooth, Type B-Embossed
Overall Thickness	4.7mm (0.1850")
Wear Layer	6mil (0.15mm)
Underlayment	1.5mm EVA(0.0591")
Edge Profile	Square edge
Surface Finish	Polyurethane Matt Coating
Embossing	Deep emboss
Edge Profile	Unilin
Size	7" W x 48" L (178x1220mm)
Square Feet Per Carton	28.05 SQFT/CTN
Pieces Per Carton	12 PIECES/Carton
Weight Per Carton	17.17 KGS/CTN 37.85 LBS/CTN
Carton Per Pallet	65 CTNS/PLT
Installation Method	Floating

TECHNICAL PROPERTY

Dimensional Stability	ASTM F2199 - Passes - ≤0.2% / lineal ft. (305 mm)
Curling	ISO 23999 - Passes - ≤2mm
Static Load	ASTM F970 - Passes - ≤0.005" (0.13mm) (without underlayer)
Static Load Limit	SIM Test - 1000 psi (0.02mm) (without underlayer)
Residual Indentation	ASTM F1914 - Passes - Average: ≤0.007" (0.18mm) (without underlayer)
Resistance to Chemicals	ASTM F925-Passes-No more than a slight change in surface
Resistance to Heat	ASTM F1514 - Passes - Average ΔE < 8.0
Resistance to Light	ASTM F1515 - Passes - Average ΔE < 8.0
Critical Radiant Flux	ASTM E648 - Passes - Class I: ≥ 0.45 W/Sq.cm
Smoke Density	ASTM E662 - Passes - Flaming & Non Flaming≤ 450
VOCs/TVOCs, Formaldehyde	CDPH/EHLB Method v1.2 Compliant
Substances of Very High Concern	REACH SVHC 191 - Passes - Per Substance: ≤0.1% w/w
Heavy Metals	ASTM F963 - Passes
Phthalates	ASTM D7823 - Passes - CPSC-CH-C1001-09.3
Slip Resistance	ASTM D2047- Dry: 0.38 Wet: 0.90
Fungi Resistance	ASTM G21-15 - Passes
IIC	ASTM E492 & ASTM E989 - Result: 73
STC	ASTM E90 & ASTM E413 - Result: 68

SUSTAINABILITY

Material	Virgin Vinyl
Certification	Floor Score® certified
Environmental Product Declaration	N/A
Health Product Declaration	N/A

SERVICE

Warranties	Limited Lifetime Warranty
www.bella flooringgroup.com	sales@bella flooringgroup.com



4001
Timrod



4002
Jefferies