



Lazio Collection

**PRODUCT DETAILS**

Product Type	Looselay
Collection	Lazio
Construction	Vinyl Looselay Plank / Vinyl Looselay Tile
Classification	ASTM F1700-Class III, Type A-Smooth, Type B-Embossed
Overall Thickness	5.0 mm (.20")
Wear Layer	22 mil (0.55 mm)
Edge Profile	Micro-bevel
Surface Finish	UV Coating
Embossing	Photo Match Embossing / Stone Embossing
Size	Plank 8" W x 48" L / 203.2 mm x 1219.2 mm Tile 12" W x 24" L / 304.8 mm x 609.6 mm
Square Feet Per Carton	21.336 sf/ctn; 22 sf/ctn
Pieces Per Carton	8 pieces/ctn; 11 pieces/ctn
Weight Per Carton	81.35 lbs/ctn; 38.25 lbs/ctn
Carton Per Pallet	70 ctns/plt; 60ctns/plt
Installation Method	Full Spread or Loose Lay

TECHNICAL PROPERTY

Dimensional Stability	ASTM F2199 -Passes- $\leq 0.020"$ / lineal ft. (305 mm)
Curling	ISO 23999 - Passes - ≤ 2 mm
Static Load	ASTM F970 -Passes- $\leq 0.005"$ (0.13mm)
Flexibility	ASTM F137 -Passes- 1" mandrel passed
Residual Indentation	ASTM F1914 -Passes- Avg $\leq 8\%$, Max 10%
Resistance to Chemicals	ASTM F925 -Passes- No more than "Slight Change"
Critical Radiant Flux	ASTM E648 -Passes- Class I: ≥ 0.45 W/Sq.cm
VOCs/TVOCs	CDPH/EHLB -Compliant
Substances of Very High Concern	REACH SVHC 191 -Per Substance: $\leq 0.1\%$ w/w
Heavy Metals	ASTM F963 -Passes
Phthalates	ASTM D7823 /CPSC-CH-C1001-09.3 -Passes
Slip Resistance	EN14041 - Result: Class DS
IIC	ASTM E492 & ASTM E989 - Result: 66
STC	ASTM E90 & ASTM E413 - Result: 67

SUSTAINABILITY

Material	Clean Recycle W/O DOTP
Certification	FloorScore® certified

SERVICE


Warranties	Limited Lifetime Warranty
------------	---------------------------



Specification Sheet



2401
Bianca+



2402
Aurora+



2403
Chiara+



2405
Viola+



2406
Marta+



2407
Sofia+



2408
Greta+



2409
Dolce+



2410
Adona+



2411
Edda+



2412
Fia+



2413
Coco+