



SAFETY DATA SHEET STYCCOBOND F41

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME STYCCOBOND F41
 INTERNAL ID SBF41/13
 APPLICATION Flooring Adhesive
 SUPPLIER F.Ball and Co. Ltd.
 Churnetside Business Park,
 Station Road,
 Cheddleton,
 Leek,
 Staffordshire. ST13 7RS
 Tel: 01538 361633 Mon-Fri
 8.30am-5.00pm (Exc Bank Holidays)
 Fax: 01538 361622
 E.mail: mail@f-ball.co.uk

2 HAZARDS IDENTIFICATION

Not regarded as a health or environmental hazard under current legislation.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
ALKYLPHENOETHERSULPHATE SODIUM SALT			1-2%	Xi;R41. R52/53.

The Full Text for all R-Phrases are Displayed in Section 16

COMPOSITION COMMENTS

Acrylic Copolymer Emulsion

4 FIRST-AID MEASURES

INHALATION

Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

INGESTION

Rinse mouth thoroughly. Drink plenty of water. Do not induce vomiting. Get medical attention if any discomfort continues.

SKIN CONTACT

Wash skin thoroughly with soap and water. Remove contaminated clothing. Get medical attention if irritation persists after washing.

EYE CONTACT

Immediately rinse with water. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

This product is not flammable. Use fire-extinguishing media appropriate for surrounding materials.

6 ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS

Use protective gloves, goggles and suitable protective clothing.

ENVIRONMENTAL PRECAUTIONS

Do not discharge into drains, water courses or onto the ground.

SPILL CLEAN UP METHODS

Small Spillages Absorb with sand or other inert absorbent. Large Spillages Dam and absorb spillages with sand, earth or other non-combustible material. Collect spillage in containers, seal securely and deliver for disposal according to local regulations. Wear necessary protective equipment.

STYCCOBOND F41**7 HANDLING AND STORAGE****USAGE PRECAUTIONS**

Provide good ventilation. Do not use in confined spaces without adequate ventilation and/or respirator. Avoid contact with skin and eyes. Observe good industrial hygiene practices. Do not eat, drink or smoke when using the product.

STORAGE PRECAUTIONS

Keep separate from food, feedstuffs, fertilisers and other sensitive material. Store in closed original container at temperatures between 5°C and 30°C. Protect from freezing and direct sunlight.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION**ENGINEERING MEASURES**

Provide adequate ventilation.

HAND PROTECTION

For prolonged or repeated skin contact use suitable protective gloves. Nitrile gloves to BSEN374 are recommended. Break through times can vary depending on thickness, use and source. Change gloves regularly.

EYE PROTECTION

If there is a risk of splashing, wear chemical resistant goggles or visor approved to BS EN166.

HYGIENE MEASURES

Good personal hygiene practices should be followed when working with chemicals.

PERSONAL PROTECTION

Always check applicability with your supplier of protective equipment.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Emulsion		
COLOUR	White		
ODOUR	Typical acrylic		
RELATIVE DENSITY	1.00-1.03 approx @ 20 degC	VAPOUR PRESSURE	23 mbar @ 20degC (water)
VOLATILE BY VOL. (%)	40 w/w approx (water)	pH-VALUE, CONC. SOLUTION	4.5-5.5
VISCOSITY	40-60 Ps @ 20 degC	FLASH POINT (°C)	N/A

10 STABILITY AND REACTIVITY**STABILITY**

Stable under normal temperature conditions and recommended use.

CONDITIONS TO AVOID

Avoid frost. Avoid exposure to high temperatures or direct sunlight.

11 TOXICOLOGICAL INFORMATION**INHALATION**

May cause some discomfort in poorly ventilated areas.

INGESTION

May cause discomfort if swallowed.

SKIN CONTACT

Prolonged contact may cause redness and irritation. Skin irritation is not anticipated when used normally.

EYE CONTACT

May cause irritation, soreness and reddening of the eyes

12 ECOLOGICAL INFORMATION**ECOTOXICITY**

There are no data on the ecotoxicity of this product.

13 DISPOSAL CONSIDERATIONS**DISPOSAL METHODS**

Dispose of waste and residues in accordance with local authority requirements. Small quantities may be absorbed in sand and allowed to dry, prior to disposal as low hazard waste. Larger quantities should be disposed of as controlled liquid waste via a licensed waste operator.

STYCCOBOND F41

WASTE CLASS

Waste Code for Product : 080410

14 TRANSPORT INFORMATION

GENERAL	The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID).		
	No transport warning sign required.		
ADR CLASS	Not classified for transportation.	MARINE POLLUTANT	No.

15 REGULATORY INFORMATION

RISK PHRASES	NC	Not classified.
SAFETY PHRASES	P13	Safety data sheet available for professional user on request.

16 OTHER INFORMATION

GENERAL INFORMATION

F.Ball and Company Ltd Technical Datasheet.

INFORMATION SOURCES

Type of Regulated Adhesive under the air Pollution Control (Volatile Organic Compounds) Regulation of Hong Kong (Indoor Carpet Adhesive).
VOC Content (ready to use) not exceeding 1g/litre.

REVISION COMMENTS

Section 16 change

REVISION DATE 10/03/10

REV. NO./REPL. SDS GENERATED 13

RISK PHRASES IN FULL

R41	Risk of serious damage to eyes.
R52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.