

TERAGREN FLOORING COMPARISON CHART

TERAGREN XCORA® STRAND BAMBOO

TERAGREN TRADITIONAL PUREFORM™ BAMBOO

| Product | Synergy® Wide Plank | Portfolio Naturals | Synergy® MPL |
|--|--|------------------------|----------------------------------|
| Hardness Rating | 160% HARDER THAN OAK | | |
| Nominal Dimensions (LxWxD") | 72.05" x 7.68" x 0.55" | 72.44" x 5.43" x 0.47" | 24, 36, 48 & 72" x 3.78" x 0.47" |
| mm Profile* | 14 mm | 12 mm | 12 mm |
| Construction | ENGINEERED | SOLID | SOLID |
| Width | EXTRA WIDE PLANK | WIDE PLANK | NARROW PLANK |
| Length | SINGLE LONG-LENGTH | SINGLE LONG-LENGTH | MULTIPLE PRECISE LENGTHS |
| Milling | MICRO BEVEL | MICRO BEVEL | MICRO BEVEL |
| Profile | SELF-LOCKING | TONGUE+GROOVE | TONGUE+GROOVE |
| Color Variation | MODERATE | MODERATE | MODERATE |
| Square Feet per Box | 23.05 | 21.865 | 22.69 |
| USDA BioPreferred | ✓ | ✓ | ✓ |
| Indoor Air Quality Rating | FLOORSORE | FLOORSORE | FLOORSORE |
| FSC® Certified | NA | NA | NA |
| LEED® IEQ 4.3 Low Emitting Materials | ✓ | ✓ | ✓ |
| LEED® MR6 Rapidly Renewable Resource | ✓ | ✓ | ✓ |
| LEED® MR7 Certified Wood | NA | NA | NA |
| CA High Performance Schools EQ2.2.3 | ✓ | ✓ | ✓ |
| Coordinating Accessories | FULL LINE OF COORDINATING STAIR PARTS & ACCESSORIES | | |
| Warranty | 25-YEAR RESIDENTIAL & 10-YEAR COMMERCIAL FINISH WARRANTY; LIFETIME STRUCTURAL WARRANTY | | |
| Installation Methods | | | |
| Float - On/Above or Below Grade | ✓ | ✓ | — |
| Nail/Cleat - On/Above Grade - No Staples | — | ✓ | ✓ |
| Glue - On/Above Grade | — | ✓ | ✓ |
| | NOTE: RECOMMENDED ADHESIVE - PREMIUM BAMBOO FLOORING ADHESIVE | | |
| Underlayment | A | A, B, C | B, C |
| Nailing Guidelines | — | A | B |
| Radiant Floor Compliant | CAN BE INSTALLED OVER RADIANT HEAT – GLUE/FLOAT ONLY | | |
| Acclimation | MINIMUM OF 48 HOURS ON-SITE IN BOX | | |
| Site RH | INSTALL INTO ENVIRONMENTS HAVING 35-55% RELATIVE HUMIDITY | | |
| Maintenance | BONAKEMI PRO SERIES HARDWOOD FLOOR CLEANER OR EQUAL | | |

| Product | Studio | Craftsman II | Signature Naturals |
|--|--|------------------------|-------------------------------------|
| Hardness Rating | 40% HARDER THAN OAK | | |
| Nominal Dimensions (LxWxD") | 75" x 7.68" x 0.55" | 75.59" x 5.43" x 0.59" | 24, 36, 48 & 72.44" x 3.62" x 0.59" |
| mm Profile* | 14 mm | 15 mm | 15 mm |
| Construction | ENGINEERED | SOLID | SOLID |
| Width | EXTRA WIDE PLANK | WIDE PLANK | NARROW PLANK |
| Length | SINGLE LONG-LENGTH | EXTRA LONG-LENGTH | MULTIPLE PRECISE LENGTHS |
| Milling | MICRO BEVEL | MICRO BEVEL | MICRO BEVEL |
| Profile | SELF-LOCKING | TONGUE+GROOVE | TONGUE+GROOVE |
| Color Variation | MOST | MODERATE | MODERATE |
| Square Feet per Box | 23.99 | 28.52 | 21.86 |
| USDA BioPreferred | ✓ | ✓ | ✓ |
| Indoor Air Quality Rating | FLOORSORE | FLOORSORE | FLOORSORE |
| FSC® Certified | ** | ** | ** |
| LEED® IEQ 4.3 Low Emitting Materials | ✓ | ✓ | ✓ |
| LEED® MR6 Rapidly Renewable Resource | ✓ | ✓ | ✓ |
| LEED® MR7 Certified Wood | ** | ** | ** |
| CA High Performance Schools EQ2.2.3 | ✓ | ✓ | ✓ |
| Coordinating Accessories | FULL LINE OF COORDINATING STAIR PARTS & ACCESSORIES | | |
| Warranty | 25-YEAR RESIDENTIAL & 10-YEAR COMMERCIAL FINISH WARRANTY; LIFETIME STRUCTURAL WARRANTY | | |
| Installation Methods | | | |
| Float - On/Above or Below Grade | ✓ | ✓ | — |
| Nail/Cleat - On/Above Grade - No Staples | — | ✓ | ✓ |
| Glue - On/Above Grade | — | ✓ | ✓ |
| | NOTE: RECOMMENDED ADHESIVE - PREMIUM BAMBOO FLOORING ADHESIVE | | |
| Underlayment | A | A | B, C |
| Nailing Guidelines | — | — | D |
| Radiant Floor Compliant | CAN BE INSTALLED OVER RADIANT HEAT – GLUE/FLOAT ONLY | | |
| Acclimation | MINIMUM OF 48 HOURS ON-SITE IN BOX | | |
| Site RH | INSTALL INTO ENVIRONMENTS HAVING 35-55% RELATIVE HUMIDITY | | |
| Maintenance | BONAKEMI PRO SERIES HARDWOOD FLOOR CLEANER OR EQUAL | | |

Underlayment

A - Float: Vapor barrier with pad over cement subfloor, vapor retarder with pad over wood subfloor
 B - Nail/Staple: Vapor retarder over wood subfloor
 C - Glue: Vapor barrier over cement subfloor, vapor retarder over wood subfloor

Nailing Guidelines

A - 18 guage cleat 1½" - 2"
 B - 18 guage cleat 1¼" - 1½"
 C - 18 guage cleat or narrow crown staple 1¼" - 1½"
 D - 15-16 guage cleat or staple 1½" - 2"

*DETERMINES COORDINATING ACCESSORIES

** AVAILABLE BY SPECIAL ORDER (MINIMUM QUANTITIES APPLY)

Complete acclimation and installation instructions are available at

www.teragren.com/downloads

TERAGREN FLOORING COMPARISON CHART II

XCORA® STRAND

TRADITIONAL PUREFORM™

| Product | Essence | Neotera | Wright Bamboo |
|---|--|--------------------------|-------------------------------------|
| Hardness Rating | 160% HARDER THAN RED OAK | 160% HARDER THAN RED OAK | AVERAGES 40% HARDER THAN RED OAK |
| Nominal Dimensions (LxWxD") | 72.83" x 7.48" x 0.55" | 72.83" x 5.12" x 0.47" | 75.59" x 7.48" x .59" |
| mm Profile* | 14 mm | 12 mm | 15 mm |
| Wear Layer | 3 mm | 2 mm | NA |
| Construction | ENGINEERED | ENGINEERED | SOLID |
| Width | EXTRA WIDE PLANK | WIDE PLANK | EXTRA WIDE PLANK |
| Length | SINGLE LONG-LENGTH | SINGLE LONG-LENGTH | SINGLE LONG-LENGTH |
| Milling | MICRO BEVEL | MICRO BEVEL | MICRO BEVEL |
| Profile | TONGUE + GROOVE | TONGUE + GROOVE | TONGUE + GROOVE |
| Color Variation | MODERATE | MODERATE | MODERATE |
| Square Feet per Box | 22.70 | 20.71 | 23.56 |
| USDA BioPreferred | ✓ | ✓ | ✓ |
| Indoor Air Quality Rating | FLOORSORE | FLOORSORE | FLOORSORE |
| FSC® Certified | ** | ** | ** |
| LEED® IEQ 4.3 Low Emitting Materials | ✓ | ✓ | ✓ |
| LEED® MR6 Rapidly Renewable Resource | ✓ | ✓ | ✓ |
| LEED® MR7 Certified Wood | ** | ** | ** |
| CA High Performance Schools EQ2.2.3 | ✓ | ✓ | ✓ |
| Coordinating Accessories | COORDINATING STAIR PARTS & ACCESSORIES | | |
| Warranty | 25-YEAR RESIDENTIAL & 10-YEAR COMMERCIAL FINISH WARRANTY; LIFETIME STRUCTURAL WARRANTY | | |
| Installation Methods | | | |
| Float - On/Above or Below Grade | ✓ | ✓ | ✓ |
| Nail/Cleat - On/Above Grade - No Staples | ✓ | ✓ | ✓ |
| Glue - On/Above Grade | ✓ | ✓ | ✓ |
| NOTE: RECOMMENDED ADHESIVE - PREMIUM BAMBOO FLOORING ADHESIVE | | | |
| Underlayment | A, B, C | A, B, C | A, B, C |
| Nailing Guidelines | A | A | A |
| Radiant Floor Compliant | NOT RECOMMENDED FOR INSTALLATION OVER RADIANT HEAT | | |
| Acclimation | MINIMUM OF 48 HOURS ON-SITE IN BOX | | |
| Site RH | INSTALL INTO ENVIRONMENTS HAVING 35-55% RELATIVE HUMIDITY | | |
| Maintenance | TRUECLEAN FLOOR CLEANER | | |

Underlayment

A - Float: Vapor barrier with pad over cement subfloor, vapor retarder with pad over wood subfloor
 B - Nail/Staple: Vapor retarder over wood subfloor
 C - Glue: Vapor barrier over cement subfloor, vapor retarder over wood subfloor

Nailing Guidelines

A - 18 or 20 guage cleat x 1.5"

*Determines coordinating accessories

** Available by special order (minimum quantities apply)