



PALL-X KITT

Water-based joint filler compound for wood floors.

Description

PALLMANN® PALL-X KITT is a water-based wood filler compound that is mixed with sanding dust and used for joint and trowel filling of wood floors. It is suitable for solid strip and plank, engineered and parquet flooring of most species where color-matching is important and where filler stability and adhesion are vital. PALL-X KITT's viscous, paste-like mixture is rated for radiant heat floor systems.

Features

- Uses sanding dust from floor to be filled
- Ready to use, fast drying formula
- No-clog formula
- High viscosity

Benefits

- Perfect color matching
- Saves time
- Will not load or waste abrasives
- Holds well in gaps



Technical Data

Packaging:	1 U.S. plastic gallon
Color:	Milky yellow when wet, color-matched to species when dry
VOC Content:	VOC does not exceed 100 grams per liter
Stability:	Minimum 12 months
Mixing Ratio:	Blend to a paste consistency that can be trowel applied
Working Temp.:	65-75°F (18-25°C) for optimum performance
Coverage Rate:	Approx. 400 sq. ft. per gallon, depending on floor condition
Ready for Sanding:	15-30 minutes
Storage:	Store between 50-70°F (10-20°C). Keep from freezing.

Directions for Use

1. Shake product well prior to mixing with, 80 – 100 grit edger or buffer sanding dust.
2. Pour the PALL-X KITT into a 'crater' of sanding dust on the floor to be filled. Using a stainless steel trowel (Item #12506), blend the liquid with the dust to achieve a trowelable paste consistency.
3. Trowel apply to the floor, filling all joints and gaps. NOTE: From time to time it will be necessary to add more KITT liquid to the mix on the floor to maintain a paste-like consistency. PALL-X KITT may also be mixed with sanding dust in a bucket prior to trowel application.

Important Notes

- The filling application should be made before the final cut with the belt or drum sander.
- The floor can normally be sanded 15 to 25 minutes after filling. High humidity and / or low temperature conditions may extend the dry time while increased ventilation and airflow may reduce dry time.
- PALL-X KITT can only be removed using a belt or drum sander. Do not try to remove using a rotary buffer sander only.
- To ensure proper color match, test filler, stain and finish in an inconspicuous area.
- Do not use with bamboo floors.

Clean Up

Tools and applicators should be cleaned with water.

Storage

Minimum 24 months in original packaging when stored under normal conditions (50-70°F/10-20°C). Tightly reseal opened containers. Keep from freezing.

Uzin Utz
NORTH AMERICA

PALLMANN | A Brand of Uzin Utz Group
Aurora, CO 80011 USA | Phone: 720. 374.4810
pallmann.us@uzin-utz.com | pallmann.us



PALLMANN®

wood floors. protected