

# FORTIBOARD® Heavy Duty Surface Protection

## SPECIFICATION GUIDE

### PART 1 - GENERAL

#### 1.01 SUMMARY

- A. Section Includes: Provides finished floor protection building paper

#### 1.02 SUBMITTALS

- A. Product Data: Submit manufacturer's FORTIBOARD® literature for each type of membrane.
- B. Samples: Submit samples of each FORTIBOARD material.
- C. Quality Assurance/Control Submittals: Submit either test reports or manufacturer's certificates indicating materials comply with specified requirements available from Fortifiber upon request.

### PART 2 - PRODUCTS

#### 2.01 MANUFACTURER

- A. Fortifiber® Building Systems Group, 1-800-773-4777.
- B. Substitutions: Comply with provisions of Division 1.

#### 2.02 MATERIALS

- A. Finished Floor Protection: Fortifiber® / Seekure® laminated glass fiber reinforced non-staining kraft building paper resistant to puncture, tears and abrasion.
  - 1. Tensile Strength: 54 lb f/in Machine Direction, 25 lb f/in Cross Machine Direction; ASTM D 828.
  - 2. Water Resistance: 5 hours minimum; ASTM D 779.
  - 3. Reference Standard: Federal Spec UU-B-790A, Type 1, Style 4

#### 3.01 PREPARATION

- A. Ensure, substrate is free of projections and irregularities which may be detrimental to proper installation of membrane.

#### 3.02 INSTALLATION

- A. Apply FortiBoard either side up, logo up is preferred for inspection, laid smooth without folds of material.
  - 1. Cut to fit area to be covered with utility knife.
  - 2. Place adjoining rolls next to each other.
  - 3. Tape Seam: Butt adjoining FortiBoard roll and tape seam to hold adjoining rolls together with Permeable FortiBoard Tape (min. 6 perm with tape on board test by ASTM D770 FortiBoard Tape. Do not tape to finished surfaces.

All values presented are determined on specimens prepared to ASTM standards. These are nominal values and should not be interpreted as specifications. The Fortifiber Building Systems Group® believes all information and data herein to be accurate and reliable.

#### Standard Product Warranty

Fortifiber Corporation warrants that its products are in compliance with their published specifications and are free from defects in materials and workmanship for a period of two years from the date of purchase. This warranty does not apply to loss due to abuse. Material found to be defective will be replaced at no charge by Fortifiber, but in no event shall Fortifiber be liable for any other costs or damages, including any labor costs.

THIS EXPRESS WARRANTY IS GIVEN IN LIEU OF AND EXCLUDES ALL OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING BUT NOT LIMITED TO THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Fortifiber's sole obligations under this warranty are as set forth herein. In no event shall Fortifiber be liable for any lost revenue or profits, direct, indirect, special, incidental or consequential damages of any kind.