

Good for athletes. Great for floors.



Inspire confidence in every area of your facility with quality flooring underfoot. Our non-vulcanized process creates tough, odorless mats without the use of harmful solvents or VOC's. Whatever comes through your door, whether it's skate blades, metal cleats, rolling loads, or rough equipment edges, Dinoflex has got you covered.



Features:

- Non-vulcanized
- Great traction - wet or dry
- Heavy duty dense material
- Ergonomic
- Impact Absorbing

Benefits:

- Certified for indoor air quality with no odor
- Prevent costly injuries from slips & falls
- Easy to clean
- Low maintenance costs
- Reduces soreness, fatigue in muscles & joints
- Decreases vibration & noise

Let Us Introduce Ourselves

Dinoflex has been a leading innovator in the manufacturing of recycled rubber products for over 30 years. We work closely with industry professionals to meet their building and flooring needs with premium quality, rubber flooring, exterior tiles, and custom products.

Size: 4' x 6'	Thickness: 7mm; 12mm; 15mm
----------------------	-----------------------------------

Vulca-NO! Sport Technical Data

TEST	RESULTS
ASTM F2569 Force Reduction	11.3%, Class 1
ASTM F2272 Standard Vertical Deformation	0.6mm, Class B
ASTM D4060 Taber Abrasion	Weight Loss 0.19% 1,000 Cycles at 1,000 Grams
ASTM D412 Tensile Strength	Breaking Load 115.98 lbs. Elongation 137.02%. Tensile 479.9 lbs/sq in.
ASTM F137 Flexibility	Passes 6mm Mandrel
ASTM F970 Static Load Limit at 250 psi	Residual Compression 0.005 Inch
EN 12235/CI Ball Rebound	98.5%, Passes
Surface Finish Effect	104 BPV Passes
Slip Resistance	Dry 0.83;
ASTM D2240 Durometer Hardness	73 Shore A

For complete specifications and technical data, please visit our website at www.dinoflex.com



Dinoflex

P.O. Box 3309
 5590 46 Ave S.E.
 Salmon Arm, B.C., Canada
 V1E 4S1

Toll Free: 1.877.713.1899
 Direct: 250.832.7780
 Email: sales@dinoflex.com

www.dinoflex.com



Represented By: