

uniquely different



# DinoTurf

by dinoflex



**Recycled**  
Rubber Flooring

Indoor Sports

Driving Ranges

CrossFit

Playgrounds

Schools



## There is no off-season with DinoTurf.

We combine ultra-durable recycled rubber with the toughest rated turf for indoor training. Our unique proprietary bonding system laminates two heavy duty layers together to create a surface that can withstand the most extreme workouts, day in and day out.

### Features:

- Long lasting fibers
- Shock absorbing
- Noise reducing
- Abrasion resistant
- No in-fill
- Low VOC emissions

### Benefits:

- Long life cycle
- Reduces muscle, back, hip and joint strain
- Quiet workout space
- Great for sled work and cardio drills
- Easy to maintain
- Improved air quality





## Luxury backing protects you and your floor.

Our impact reducing recycled rubber backing decreases muscle fatigue and impact on joints, while absorbing the shock and wear of repetitive footfalls, dropped weights, and heavy equipment. In spaces with training sleds or rolling loads, tiles can be glued down, ensuring your floor outlasts the competition.

### Applications:

- CrossFit Gym
- Fitness Center
- Indoor arena overlay
- Indoor sports facility
- Putting green
- Driving range
- Playgrounds
- Multi pet applications

### Thickness available:

16mm turf laminated to luxury backing:

- 22mm = 16mm + 6mm
- 24mm = 16mm + 8mm
- 26mm = 16mm + 10mm

### Size:

- 38" x 38" Square Cut glue down
- 37" x 37" Interlocking loose lay

# Let Us Introduce Ourselves

Dinoflex has been a leading innovator in the manufacturing of recycled rubber products for over 25 years. We specialize in producing premium quality rubber flooring, exterior tiles and custom products. Our merchandise provides solutions for architects, designers and builders that are cost effective and environmentally friendly.

## LEED – Leadership in Energy and Environmental Design

Dinoflex recycled rubber products help qualify for LEED credits.

Please refer to [www.dinoflex.com](http://www.dinoflex.com) for more information.

### DinoTurf Technical Data

CATEGORY	RESULTS	TEST	RESULTS
Pile height	16mm	ASTM D 5034 Grab Tear Strength	Breaking Load: Warp (length) 375.6 Lbs. Fill (width) 450.8 Lbs.
Density	77700	ASTM D 7138 Yarn Melting Point	172°C Melting Point; indicates Polypropylene
Dtex	6500	ASTM D 2859 Flammability	Passes
Coating	SBR Coating	ASTM E 84 Surface Burning Characteristics (Smoke Density)	Flame Spread Index = 110 Smoke Development Index = 950
Fiber Thickness	Average Thickness: 0.112 mm Average Width: 0.911 mm	ASTM F 2569 Force Reduction	Force Reduction 26.8%, Vertical Deformation 3.1mm
Color	Solid Green	ASTM F 1292 Impact Attenuation / G-Max	GMAX 178; HIC 995; 4.5' Fall Height
Application	Indoor and outdoor use		

For complete specifications and technical data, please visit our website at [www.dinoflex.com](http://www.dinoflex.com)

**5 YEAR WARRANTY**



#### Dinoflex

P.O. Box 3309  
5590 46 Ave S.E.  
Salmon Arm, B.C., Canada  
V1E 4S1

Toll Free: 1.877.713.1899  
Direct: 250.832.7780  
Email: [sales@dinoflex.com](mailto:sales@dinoflex.com)

[www.dinoflex.com](http://www.dinoflex.com)



Represented By: